DOCUMENT RESUME

BD 103 263 SE 018 642

TITLE The Incinerator: Section Two, Maintenance and Trobuleshooting. Part 6, Air Pollution Training

Institute Self-Instructional Course SI-466.

INSTITUTION Environmental Protection Agency, Research Triangle

Park, N.C. Air Pollution Training Inst.; Sage (David)

Inc., New York, N.Y.

PUB DATE 73

NOTE 41p.: Related documents are SE 018 637-643

EDRS PRICE MF-\$0.76 HC-\$1.95 PLUS POSTAGE

DESCRIPTORS *Air Pollution Control; *Autoinstructional Aids;

*Environmental Education; Environmental Technicians;

*Independent Study; *Pollution; Post Secondary Education: Programed Instruction; Programed

Materials

IDENTIFIERS *Incinerators

ABSTRACT

This workbook is part six of a self-instructional course prepared for the United States Environmental Protection Agency. The student proceeds at his own pace and when questions are asked, after answering, he either turns to the next page to check his response or refers to the previously covered material. The purpose of this course is to prepare the student for the APC Training Certificate. This section covers tasks that should be done daily to keep the incinerator system running smoothly and maintenance tasks to be performed periodically. Troubleshooting checks are also included. (BT)



U.S. DEPARTMENT OF HEALTH.
EDUCATION & WELFARE
NATIONAL INSTITUTE OF
EDUCATION

EDUCATION

THE DETECTION HAS BEEN REPRODUCED EXACTLY AS REFEIVED FROM THE PENNON UR WIGANIZATION URIGINATION OF STATED DO NOT NECESSARIA Y REPRESENT OFFICIAL NATIONAL INSTITUTE OF EDUCATION POSSITION OR POLICY

BEST COPY AVAILABLE



Air Pollution Training Institute Self-Instructional Course SI-466

Part 6 The Incinerator: Section Two Maintenance and Troubleshooting



Training Manual
Self-Instructional Course SI-466

Air Pollution Training Institute





United States
Environmental Protection Agency
Contract No. 68-02-0321
David Sage, Inc.
New York City, New York

Part Six
The Incinerator:
Section Two
Maintenance and Troubleshooting

David Sage, Project Manager, DSI
Mariland Ruppart, Writer Analyst, DSI
C. George Segeler, P. E., Staff Engineer, DSI
and
William Todd, Project Officer, USEPA


Prepared for the United States Environmental Protection Agency Office of Air and Water Programs Control Programs Development Division Air Pollution Training Institute



US EPA

This is not an official policy and standards document. The opinions, findings, and conclusions are those of the authors and not necessarily those of the United States Environmental Protection Agency. Every attempt has been made to represent the present state of the art as well as subject areas still under evoluation. Any mention of products, or organizations, does not constitute endorsement by the United States Environmental Protection Agency.





Additional units of this self-instructional course are:

PART ONE The Basics of Preventing Air Pollution Emissions from Boilers

PART TWO
The Basics of Boiler Operation
and Maintenance

PART THREE
Troubleshooting, Section One
Boilers: Correcting Oil Temperature

PART FOUR Troubleshooting, Section Two Boilers: Flame Reading

PART FIVE The Incinerator: Section One Basic Parts and Fundamentals

SUPPLEMENT A: Operator's Manual, Boiler Room Operations and Maintenance



INTRODUCTION

In the first incinerator section you saw the basic incinerator parts and how they operate.

This section will cover tasks you should do each day to keep the system running smoothly and maintenance tasks to be performed periodically. Also included are troubleshooting checks to make before calling service should you get smoke.

First - daily cleaning tasks.




DAILY CLEANING

Daily Cleaning reduces your chances of producing smoke. Your system will not work smoothly if clogged with waste from burning.

Set a time each day to clean and check the incinerator. WAIT AT LEAST ONE HOUR after a burn for the furnace to cool, SHUT DOWN THE SYSTEM by pushing the stop button.

BELOW ARE THREE PLACES to clean,






1.	How long should you wait after a burn to clean the incinerator?	
2.	From Kinere would you clean cans, bottle, and other large waste materrial?	
3.	From where would you clean most of the ash?	



- 1. 1 hour or more
- 2. Grate
- 3. Ash Pit

On this diagram, MARK AN "X" on the number of SEPARATION CHAMBERS that you have on your system. Leave this blank if you have none.




You may also have a roof settling chamber. Some systems have the scrubber and chambers on the roof.

Name the three places covered so far to	
be cleaned each day.	



DAILY SCRUBBER CLEANING



- 1. Where will most of the fly ash in the settling tank collect?
- 2. What must be cleaned to prevent the discharge water line from clogging?





1.	sump
----	------

2. strainer

DAILY CLEANING REVIEW

ANSWER THESE QUESTIONS:

1. Name three places in the incineral (other than the scrubber) to classical day.	
each day.	
2. Name two places in the scrubber clean daily.	to
3. How long should you wait after burn to clean your system?	er a

CIRCLE THE CORRECT WORDS below:

- 4. Turn your system ON/OFF before cleaning.
- 5. After cleaning be sure to OPEN/CLOSE all incinerator doors.



ANSWERS TO PREVIOUS PAGE:


- 1. Grate
 Ash Pit
 Separation Chambers
- 2. Sump Strainer
- 3. 1 hour
- 4. OFF
- 5. CLOSE

DAILY CHECKS

In addition to cleaning, there are some DAILY CHECKS to make to keep major parts in good working order.

CYCLING TIME CLOCK

ON THIS CLOCK, CIRCLE THE TIMES YOUR CLOCK IS SET to start a burn:



The clock is important as it brings together burning ingredients - garbage, air, ignition. If your clock isn't working, call service to fix it.

Whom do you call for incinerator service?	
Do you have his number at a conven- ient place for easy access?	
Incinerator service agencies usually repair all equipment. What is the first daily check to make?	



FUEL GATE


Next, check the CHARGING FLUE GATE.

Assume the following for the cases below:


Time clock is set at 10:00 A.M. and is working.

Time is now 10:30 A.M.

CIRCLE THE CORRECT WORDS under each:



1.
Charging gate apparently
JAMMED/WORKING



2.
Charging Gate apparently
JAMMED/WORKING



The first incinerator has started to burn and is OK. The second is jammed in the open position. It could also jam closed or partially open.

If the charging gate becomes jammed, check to see if GARBAGE is BLOCKING the gate or track. If not, the ACTUATOR PISTON may not be working. It is usually operated by water pressure. If your basic utilities (electric supply, city water pressure) are OK, call service.

<u> </u>



1. Garbage blocking gate
Actuator Piston working

dependable ignition?

2. Cycling Time Clock Charging Flue Gate

LAST TWO DAILY CHECKS:

BLOWER MOTOR – OVERFIRE AIR	Sound normal?
GAS BURNER	Sound normal? Spark Plugs connected? Gas cock open?


You will normally not have problems with the above, but they are important. Be sure they are in good working order.

 What air source has movable parts and should be checked daily? 	
2. What part is checked to confirm	



- 1. Blower Overfire Air
- 2. Gas Burner

COMPLETE DAILY INCINERATOR CHECKS BELOW:



NOW - two daily scrubber checks.




- 1. Cycling Time Clock
- 2. Charging Flue Gate
- 3. Overfire Air Blower
- 4. Gas Burner

SCRUBBER-DAILY CHECKS

TWO SCRUBBER CHECKS:

- 1. WATER CIRCULATION water moving vigorously; in and out at proper rate.
- 2. FAN AND MOTOR WORKING gases taken from the scrubber and out the flue.

On the diagram WRITE THESE TWO on the appropriate lines.



Water must circulate to clean the gases. The fan (at the top) pulls off gases for discharge. You may have a WATER LEVEL GAUGE to monitor scrubber water.	
1. Is there a water level gauge on your system?	
2. How does your scrubber circulate the water (pump, draft pressure, other)?	
3. What equipment pushes Scrubber gases out the flue which should be checked daily?	
	- Check your answers.



- 1. check your own answer
- 2. check your own answer
- 3. Fan (and motor)

REVIEW - DAILY CHECKS

1,	Cycling	
2.	Charging	
3.	Overfire Air —	
4.	Gas	
5.	Scrubber —	Circulation
6.	Scrubber -	and Motor.

If you find any sign of trouble which you cannot easily fix, call service before it develops into a major problem.



- 1. Cycling Time Clock
- 2. Charging Flue Gate
- 3. Overfire Air Blower

- 4. Gas Burner
- 5. Scrubber Water Circulation
- 6, Scrubber Fan and Motor

This completes the DAILY CLEANING and CHECKING TASKS; they are summarized below.

DAILY CLEANING

- 1. Grate
- 2. Ash Pit
- 3. Separation Chambers
- 4. Scrubber Sump
- 5. Scrubber Water Line Strainer

DAILY CHECKS

- 1. Cycling Time Clock
- 2. Charging Flue Gate
- 3. Overfire Air Blower
- 4. Gas Burner
- 5. Scrubber Water Circulation
- 6. Scrubber Fan and Motor

THESE ARE INCLUDED IN YOUR INCINERATOR HANDBOOK, PAGE 9 FOR YOUR FUTURE REFERENCE.




PERIODIC MAINTENANCE

There are three cleaning tasks to be done periodically apart from the scrubber. These are: 1) ASH BUILD-UP, 2) CHARGING FLUE PURGE, and 3) SPARK ARRESTOR.

ASH BUILD UP

Even though you regularly clean ash from the floors of your system, there will be build-up on the CHAMBER WALLS and LEDGES.

DRAW LINES ALONG SURFACES on the diagram which you should clean periodically.



You should have indicated ALL INSIDE BURNING AND SEPARATION CHAMBER WALLS AND LEDGES. You normally reach these through access doors.

How many chambers do you have to periodically clean for ash build-up?




DOUBLE FLUE - PURGE CHARGING FLUE

This task is done only in the case of a double flue incinerator.

As garbage goes down the Charging Flue, a certain amount of GREASE collects on the WALLS and attracts INSECTS.

Look at these flue. ANSWER THE QUESTIONS BELOW:



Flue C has garbage and gases passing through and is cleaned with each burn. Flue A must be cleaned by purging.



Here's how to purge the charging flue:

- 1. PUT SYSTEM ON MANUAL CONTROL
- 2. TURN SCRUBBER OFF
- 3. OPEN BY-PASS DAMPER
- 4. OPEN PURGE DAMPER
- 5. OPEN CHARGING GATE
- 6. TURN GAS BURNER ON

In the list above, CIRCLE THE TWO DAMPERS to be opened for purging.

If the charging gate is not open, the hot gases cannot enter the flue. You should have circled by-pass and purge in the above list.


1. What provides heat (hot gases) for purging?	
What are the two maintenance tasks seen so far to be performed periodically?	
Cany:	



- 1. Gas Burner
- 2. Clean ash build-up Purge charging flue

CLEAN SPARK ARRESTOR

Here are two spark arrestors. ANSWER THE QUESTIONS under them.



Does A or B show a spark arrestor that may interfere with flue gases?

Does A or B show a spark arrestor that is in good condition?

The second spark arrestor above news to be cleaned with a wire brush. The build-up may interfere with some flue gases.

Name three maintenance tasks to be performed periodically in your incinerator.




SCRUBBER MAINTENANCE

All Scrubbers are different. There are three tasks you should perform periodically on yours no matter what the type.

Before cleaning - TURN SCRUBBER OFF.

TWO PERIODIC CLEANING TASKS are on this diagram






1.	What do you clean to be sure you have a good water curtain?	
2.	What ash-collecting area should be cleened periodically in the scrubber?	
3.	What valve should be checked for adequate water control?	•



- 1. Spray nozzles
- 2. Seatling tank
- 3. Make-up water valve

On the diagram, LABEL TWO SCRUBBER MAINTENANCE TASKS just considered.



CHECK AND CORRECT YOUR DIAGRAM using the diagram on the previous page.

The THIRD SCRUBBER MAINTENANCE TASK is shown on the diagram above.

checked for good operation?	
2. What may need to be done to the	


- Check your answers.



by-pass damper?

SCRUBBER MAINTENANCE TASKS

On the diagram, LABEL THREE SCRUBBER MAINTENANCE TASKS just considered.



- Check your answers.,



- 1. Clean spray nozzles
- 2. Clean settling tank
- 3. Clean/lubricate by-pass damper

PERIODIC MAINTENANCE CHECKS FOR THE INCINERATOR/SCRUBBER ARE SUM-MARIZED BELOW:

- 1. Clean Ash Build-Up from Walls
- 2. Purge Charging Flue
- 3. Clean Spark Arrestor
- 4. Clean Spray Nozzles Scrubber
- 5. Clean Settling Tank Scrubber
- 6. Clean/Lubricate By-Pass Damper


These maintenance tasks are listed on page 9 of the Incinerator Handbook for your future reference.



TROUBLESHOOTING

Even a well-run incinerator produces smoke or odors at times. If this happens, check four things which may help you solve the problem. If not, call service.

FIRST - CHECK THE SCRUBBER



If waste gases aren't being pulled from the scrubber, the by-pass damper will automatical open and that means smoke. The gases cannot be cleaned if the water isn't vigorousiy cleanin them.




1	If you get smoke, what do you check to see if the gases are being cleaned properly?	
2 . \	What two things can you check in the scrubber for proper operation?	



- 1. Scrubber
- 2. Fan

Water

If the Scrubber is OK, check the OVERFIRE AIR and the CHARGING FLUE GATE.



The sound of the BLOWER generally tells you if it is operating properly. If the CHARGING FLUE GATE is stuck, you may be able to remedy the situation without calling service.




 What could be stuck in an open or closed position which may cause smoke? 	
2. Which major air supply can cause smoke if the blower is not working properly?	
3. What are three troubleshooting checks to make in the incinerator should you get smoke?	
	- Check your answers.



- 1. Charging flue gate
- 2. Overfire air
- 3. Scrubber
 Charging flue gate
 Overfire air

The last troubleshooting check before calling service — THE GAS BURNER. If the burner is not running properly, smoke will probably result. A problem here generally means calling service. You should check it out, however, as part of your information when calling service.

On the diagram below, LABEL THE FOUR TROUBLESHOOTING CHECKS to make before calling service when you get incinerator smoke.



 Check these with the list on the following page.



INCINERATOR TROUBLESHOOTING CHECKS before calling service:

- 1. Scrubber
- 2. Overfire Air (Blower)
- 3. Charging Flue Gate
- 4. Gas Burner

These are included on page 9 of the Incinerator Handbook for your future reference.



INCINERATOR SUMMARY

DAILY CLEANING TASKS

- 1. Grate
- 2. Ash Pit
- 3. Separation Chambers
- 4. Scrubber Sump
- 5. Scrubber Water Line Strainer

DAILY CHECKING TASKS

- 1. Cycling Time Clock
- 2. Charging Flue Gate
- 3. Overfire Air Blower
- 4. Gas Burner
- 5. Scrubber Water Circulation
- 6. Scrubber Fan and Motor

PERIODIC MAINTENANCE

- 1. Clean Ash Build-up (all inside surfaces)
- 2. Purge Double Flue Incinerators Charging Flue
- 3. Clean Spark Arrestor
- 4. Scrubber Clean Spray Nozzies
- 5. Scrubber Clean Settling Tank
- 6. Scrubber Clean/Lubricate By-Pass Damper

TROUBLESHOOTING PROCEDURE

- 1. Scrubber
- 2. Overfire Air
- 3. Charging Flue Gate
- 4. Gas Burner



REVIEW QUESTIONS: PART VI-INCINERATOR II

1,	Where will most of the ash collect from which it must be cleaned each day?	
2.	How often should the grate of the incinerator be cleaned?	
3.	From what two places in the scrubber should you clean residue each day?	
4.	What is the minimum length of time	
	you should wait after a burn to clean the incinerator?	
5.	What device should be checked daily to be sure all burning ingredients are brought together properly and on time?	
6.	What may become jammed which would result in incomplete garbage drop or firing chamber not being closed off?	
7.	Which air supply is most susceptible to problems and should be checked each day?	
8.	Should the gas burner be checked daily or only periodically?	
9.	What scrubber part should be checked each day to insure proper flue gas removal?	
10.	The action of what basic scrubber supply should be checked daily?	
I 1.	If separation chamber floors are cleaned each day, ash build-up maintenance tasks will not be necessary. (TRUE or FALSE)	



12.	In a double flue incinerator, what must be done periodically to the charging flue?	
	What device at the top of the stack must be cleaned periodically?	
14.	What scrubber part should you clean periodically to be sure you get a good water curtain?	
15.	The scrubber settling tank should be cleaned DAILY, PERIODICALLY, YEARLY. (CHOOSE ONE)	,
16.	What should be periodically done to the by-pass damper?	
17.	If you get smoke, what gas cleaning device should you first check?	
18.	What Overfire Air device should be checked in the event of smoke?	
19.	When troubleshooting smoke in the incinerator, should you check the Charging Flue Gate Gas Burner, or both?	



ANSWERS TO REVIEW QUESTIONS:

- 1. ash pit
- 2. every day
- 3. sump
- 4. 1 hour
- 5. cycling time clock
- 5. overfire air
- 8. daily
- 9. fan
- 10. water
- 11. False
- 12. purge it
- 13. spark arrestor
- 14. water nozzles
- 15. periodically
- 16. cleaned and lubricated
- 17. scrubber
- 18. blower
- 19. both

